

NATIONAL TYPE EVALUATION PROGRAM

Certificate of Conformance for Weighing and Measuring Devices

For: Computing Scale Non-computing Scale, Load Cell Electronic Model: Q1-x Series n<sub>max</sub>: 3000 e<sub>min</sub>: See table on page 2 Capacity: 3-30 kg / 6-60 lb (See table on page 2) Platform: 250 mm X 215 mm Stainless Steel Accuracy Class: III Submitted By:

Gravity Measurement, Inc. 611 Rotterdam Industrial Park Schenectady NY 12306 Tel: 518-526-5942 Contact: Z. Rick Pang Email: <u>Pang@gravitymeasurement.com</u> Web site: <u>www.gravitymeasurement.com</u>

### **Standard Features and Options**

Automatic Zero Tracking (AZT) Initial Zero Setting Mechanism (IZSM) Semi-Automatic Zero (Push Button) Semi-Automatic Tare (Push Button) Keyboard Tare Programmable Tare Price Computing (model Q1-P) Weighing (model Q1-W) Counting (model Q1-C)\* AC Power Supply DC/Battery Power Supply Liquid Crystal Display (LCD) RS-232 Communication Port Single Range Multi (Dual) Range

\*Model Q1-C must be marked "The counting feature is not legal for trade" on both the operator and customer sides.

Load Cells Used: ZEMIC Model L6D Series (NTEP Certificate of Conformance number 11-012) or other metrological equivalent and NTEP certified.

Temperature Range: -10 °C to 40 °C (14 °F to 104 °)

This device was evaluated under the National Type Evaluation Program and was found to comply with the applicable technical requirements of "NIST Handbook 44: Specifications, Tolerances and Other Technical Requirements for Weighing and Measuring Devices." Evaluation results and device characteristics necessary for inspection and use in commerce are on the following pages.

Kristin Maeey Chairman, NCWM, Inc.

Jerry Buendel Committee Chair, National Type Evaluation Program Committee Issued: May 23, 2017

#### 1135 M Street, Suite 110 / Lincoln, Nebraska 68508

The National Conference on Weights and Measures (NCWM) does not approve, recommend or endorse any proprietary product or material, either as a single item or as a class or group. Results shall not be used in advertising or sales promotion to indicate explicit or implicit endorsement of the product or material by the NCWM.



# Gravity Measurement, Inc.

Computing Scale / Q1-x Series

Maximum Capacity	Division size d	n <sub>max</sub>	Accuracy Class
3 kg / 6 lb	1 g / 0.002 lb	3000	III
6 kg / 15 lb	2 g / 0.005 lb	3000	III
15 kg / 30 lb	5 g / 0.01 lb	3000	III
30 kg / 60 lb	10 g / 0.02 lb	3000	III
1.5 kg / 3 kg or 3 lb / 6lb	0.5 g / 1 g or 0.001 lb / 0.002 lb	3000 / 3000	Ш
3 kg / 6 kg or 6 lb / 15 lb	1 g / 2 g or 0.002 lb / 0.005 lb	3000 / 3000	III
6 kg / 15 kg or 15 lb / 30 lb	2 g / 5 g or 0.005 lb / 0.01 lb	3000 / 3000	III
15 kg / 30 kg or 30 lb/ 60 lb	5 g / 10 g or 0.01 lb / 0.02 lb	3000 / 3000	III

Application: For use in general purpose weighing applications.

Identification: The required information is on a label affixed to the left side of the scale base.

<u>Sealing</u>: There are two rods protruding through the underside of the scale which have holes drilled through them. Wire security seals are to be affixed to each rod to prevent separation of the housing from the base.

**Test Conditions:** This certificate is issued based upon the following tests and upon information provided by the manufacturer. For the purposes of this evaluation, a model Q1-P 6 lb x 0.002 lb capacity, a model Q1-W 60 lb x 0.02 lb capacity, a model Q1-P 1.5/3 kg capacity and a model Q1-W 15/30 kg were submitted. The emphasis of the evaluation was on the design, marking, operation and compliance with influence factor requirements. Several increasing/decreasing load tests and shift tests were performed on each device. The devices were tested with an AC power supply from 102 VAC to 132 VAC and a DC power supply from 4 VDC to 6.6 VDC. The devices were tested over a temperature range of -10 °C to 40 °C (14 °F to 104 °F). A load of approximately one-half capacity was applied to the units over 100 000 times (each) and the scales were tested periodically during this time.

## Evaluated By: E. Morabito (NY)

**Type Evaluation Criteria Used:** *NIST Handbook 44 Specifications, Tolerances, and Other Technical Requirements for Weighing and Measuring Devices, 2017 Edition. NCWM Publication 14 Weighing Devices, 2017 Edition.* 

<u>Conclusion</u>: The results of the evaluation and information provided by the manufacturer indicate the device complies with applicable requirements.

Information Reviewed By: J. Truex (NCWM)

## **Examples of Device:**







Method of Sealing